

Model CS5-36 COOL-SPACE™ Portable Evaporative Cooler

SPECIFICATION SHEET



Housing - Constructed of roto-molded corrosion free polyethylene mounted on 4" casters.

Cooling Media - 8" thick high efficiency cross-corrugated angle fluted specially formulated cellulose material treated with a thermosetting resin

Fan - 36 inch industrial duty aluminum or galvanized steel 4-blade construction for quieter operation.

Fan Motor - High efficiency, totally enclosed 3/4 h.p.

1 - Speed: 11,000 CFM @ .0" S.P.

9,500 CFM @ .15" S.P.

3 - Speed: 11,000 CFM @ .0" S.P.

High: 9,500 CFM @ .15" S.P.

Med: 7,500 CFM @ .15" S.P.

Low: 5,900 CFM @ .15" S.P.

1 - Speed Direct Drive: 115 volt / 1 p.h. / 6.4 amps

3 - Speed Belt Drive: 115 volt / 1 p.h. /

Amps: High 8.9 / Med. 6.3 / Low 3.2

Circulation Pump - Submersible maintenance free
115 volt / 1 p.h. / 5.0 amps

Water Supply - Garden hose connection or portable supply tank. Level regulated by float valve.

Water Reservoir - Internal 46 gallon capacity.

Cooling Coverage Area - Approx. 2,500 sq. ft.

Dimensions - 62" Wide x 31 1/2" Deep x 69" Height

Shipping Weight - 325 lbs.

2-YEAR Warranty - See Owners Manual for details.



MODELS:

CS5-363B - 3-Speed Belt Drive

CS5-361D - 1-Speed Direct Drive



Advanced Radiant Systems, Inc.
12910 Ford Drive - Fishers, IN 46038
Tel. (317) 577-0417 - Fax. (317) 842-3989
TF. (800) 557-5716 - www.cool-space.com